

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

### Listing of Claims:

1. (Currently Amended) A method for fail-safe renaming of logical circuit identifiers for rerouted logical circuits in a data network, the method comprising:  
providing a network management module;  
for renaming a first logical circuit identifier for a first logical circuit in the data network to a second logical circuit identifier for a second logical circuit utilized for rerouting data from the first logical circuit in the data network; and  
receiving a customer report indicating a network circuit failure in the data network, wherein indicating a network failure comprises receiving trap data indicating the network circuit failure, wherein the trap data comprises status information indicating that a switch in the data network is discarding frames or cells;  
identifying, in response to the customer report, a failure in the logical circuit; and  
renaming, in response to the failure, a logical circuit label for the first logical circuit in a logical element module in communication with the network management module,  
wherein the renamed logical circuit label is utilized to indicate that the logical circuit data from the first logical circuit has been rerouted, and  
wherein the renamed logical circuit label includes the status of the failed logical circuit and indicates that the logical circuit identified by a customer ID for communicating data between a first and second location has been rerouted.

2. (Original) The method of claim 1, wherein renaming a first logical circuit identifier for a first logical circuit in the data network to a second logical circuit identifier for a second logical circuit utilized for rerouting data from the first logical circuit in the data network, comprises:

accessing a network device provisioned for routing data over the first logical circuit in the data network;

deleting the first logical circuit in the network device upon detecting a failure in the first logical circuit;

provisioning the second logical circuit in the network device for rerouting the data from the first logical circuit, wherein provisioning the second logical circuit includes assigning the second logical circuit identifier to identify the second logical circuit; and

renaming the first logical circuit identifier to the second logical circuit identifier.

3. (Original) The method of claim 1, wherein the second logical circuit is a logical failover circuit in the data network.

4. (Previously Presented) The method of claim 1, wherein the second logical circuit is a currently unused logical circuit in the data network.

5. (Original) The method of claim 1, wherein the first logical circuit identifier is a data link connection identifier (DLCI).

6. (Original) The method of claim 1, wherein the second logical circuit identifier is a data link connection identifier (DLCI).

7. (Original) The method of claim 1, wherein the first logical circuit identifier is a virtual path/virtual circuit identifier (VPI/VCI).

8. (Original) The method of claim 1, wherein the second logical circuit identifier is a virtual path/virtual circuit identifier (VPI/VCI).

9. (Original) The method of claim 1, wherein the first and second logical circuits are permanent virtual circuits.

10. (Original) The method of claim 1, wherein the first and second logical circuits are switched virtual circuits.

11. (Original) The method of claim 1, wherein the data network is a frame relay network.

12. (Original) The method of claim 1, wherein the data network is an asynchronous transfer mode (ATM) network.

13. (Currently Amended) A system for fail-safe renaming of logical circuit identifiers for rerouted logical circuits in a data network, the system comprising:

a network device for establishing a communication path for a logical circuit and a logical failover circuit in the data network;

a logical element module in communication with the network device for configuring the logical circuit and the logical failover circuit; and

a network management module, in communication with the logical element module, for:

receiving a customer report indicating a network circuit failure in the data network, wherein indicating a network failure comprises receiving trap data indicating the network circuit failure, wherein the trap data comprises status information indicating that a switch in the data network is discarding frames or cells;

identifying, in response to the received customer report, a failure in the logical circuit;

deleting the communication path for the failed logical circuit in the network device;

establishing the communication path for the logical failover circuit to reroute the data from the failed logical circuit;

assigning a logical failover circuit identifier to identify the logical failover circuit;

renaming a logical circuit identifier for the failed logical circuit to the logical failover circuit identifier in the network database; and

renaming, in response to the failure, a logical circuit label for the failed logical circuit in the logical element module,

wherein the renamed logical circuit label is utilized to indicate that the logical

circuit data from the failed logical circuit has been rerouted, and

wherein the renamed logical circuit label includes the status of the failed logical circuit and indicates that the logical circuit identified by a customer ID for communicating data between a first and second location has been rerouted.

14. (Original) The system of claim 13, wherein the logical circuit identifier is a data link connection identifier (DLCI).

15. (Original) The system of claim 13, wherein the logical failover circuit identifier is a data link connection identifier (DLCI).

16. (Original) The system of claim 13, wherein the logical circuit identifier is a virtual path/virtual circuit identifier (VPI/VCI).

17. (Original) The system of claim 13, wherein the logical failover circuit identifier is a virtual path/virtual circuit identifier (VPI/VCI).

18. (Original) The system of claim 13, wherein the logical circuit and the logical failover circuit are permanent virtual circuits.

19. (Original) The system of claim 13, wherein the logical circuit and the logical failover circuit are switched virtual circuits.

20. (Original) The system of claim 13, wherein the data network is a frame relay network.

21. (Original) The system of claim 13, wherein the data network is an asynchronous transfer mode (ATM) network.

22. (Currently Amended) A method for fail-safe renaming of logical circuit identifiers for rerouted logical circuits in a data network, the method comprising:

providing a network management module for:

receiving a customer report indicating a network circuit failure in the data network, wherein indicating a network failure comprises receiving trap data indicating the network circuit failure, wherein the trap data comprises status information indicating that a switch in the data network is discarding frames or cells;

identifying, in response to the customer report, a failure in the logical circuit;

accessing, in response to the failure, a network device provisioned for routing data over a first logical circuit in the data network;

deleting the first logical circuit in the network device upon detecting a failure in the first logical circuit;

provisioning a second logical circuit in the network device for rerouting the data from the first logical circuit, wherein provisioning the second logical circuit includes assigning a second logical circuit identifier to identify the second logical circuit; and

renaming a first logical circuit identifier to the second logical circuit identifier;

and

renaming a logical circuit label, in response to the failure, for the first logical circuit in a logical element module in communication with the network management module,

wherein the renamed logical circuit label is utilized to indicate that the logical circuit data from the first logical circuit has been rerouted, and

wherein the renamed logical circuit label includes the status of the failed logical

circuit and indicates that the logical circuit identified by a customer ID for communicating data between a first and second location has been rerouted.